

# Securefašt

## CONSTRUCTION PRODUCTS REGULATION (EU) 305/2011 DECLARATION OF PERFORMANCE

DoP N° 0014-SEZ905-006

1. Unique identification code of the product type:

**SEZ905.1 64mm Qube Bathroom Lock, 5mm spindle PB,  
SEZ906.1 76mm Qube Bathroom Lock 5mm spindle PB,  
SEZ905.2 64mm Qube Bathroom Lock, 5mm spindle SC,  
SEZ906.2 76mm Qube Bathroom Lock 5mm spindle SC.**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

**SEZ905.1 64mm Qube Bathroom Lock, 5mm spindle PB,  
SEZ906.1 76mm Qube Bathroom Lock 5mm spindle PB,  
SEZ905.2 64mm Qube Bathroom Lock, 5mm spindle SC,  
SEZ906.2 76mm Qube Bathroom Lock 5mm spindle SC.**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**When used with an appropriate door closing device on fire and/or smoke control doors to fulfil the self-closing requirement of such doors, and thereafter to ensure that the door remains shut.**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5):

**Securefast plc  
Unit 6, The Cedar Business Centre  
Avon Road, Cannock, Staffs, WS11 1QJ United Kingdom  
Tel: +44 (0) 1543 501 600  
Fax: +44 (0) 1543 501 601**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**N/A**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 1**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 12209:2003**

**Notified testing laboratory No 1121 performed the type testing and issued test reports**

8. European Technical Assessment:

**N/A**

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
<b>Self-closing ability</b> -5.4.2 Closing force -5.1.2 Return force of latch bolt	Grade 8, up to 200kg door mass, 15 N max. closing force $\leq 15 \text{ N}$ $\geq 2,5 \text{ N}$	<b>EN 12209:2003</b>
<b>Durability of self-closing action</b> -5.3.1 Durability of latch action	Grade H: 50 000 test cycles with 25 N load on the latch bolt	
<b>Ability to maintain door in closed position and not contribute to the spread of fire</b> -5.5 Suitability for use on fire/smoke doors	Grade 1: suitable for use on fire/smoke resisting doorset assemblies	
<b>Control of dangerous substances</b> -5.1.1 Dangerous substances	The materials in this product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Mr Kevin O'Reilly DipGAI MInstAI RegAI  
 Operations Director

31st May 2013

Unit 6, The Cedar Business Centre,  
 Avon Road, Cannock, Staffs, WS11 1QJ  
 United Kingdom