

Electronic Side Load Lock – ADA66/ASA66



ADA66 Double Action



ASA66 Single Action

The motor driven Electronic Side Load Lock is available for single or double acting doors in both commercial and residential areas of a building.

The lock addresses the two biggest issues in door locking, the ability to align a misaligned door and the ability to release when requested, even with excessive load on the bolts. The electronic lock is reliable, secure and convenient.

The side door lock can convert from Fail Safe to Fail Secure by repositioning a single jumper. The door can have in excess of 100kg being applied and it will still release instantly when requested.

Certification

- EN61000-6-1: 2007
- EN61000-6-3: 2007 + Amendment 1: 2001
- FCC Part 15, subparts A and B
- Patent pending: PCT/IB2013/053737
- Fire test in accordance BS 476:Part 22-1987

Product Code

ADA66	Double Action Motor Driven Lock
ASA66	Single Action Motor Driven Lock

Features & Benefits

- Door misalignment of up to ± 8 mm is corrected
- Automatic Deadbolting
- 10,000N holding force (1000kg)
- Two, 10mm thick stainless bolt pins
- Input voltage from 12v DC – 24v DC
- Less than 50mA standby current
- Reverse polarity and transient protection
- Multiple attempts to lock
- Door and bolt position monitors
- Mortice mount horizontally or vertically, on double or single acting doors
- Surface mount with the aid of the accessories, including mounting onto glass
- Single Lock dimensions H160mm x W30mm x D51mm
- Double Lock dimensions H255mm x W30mm x D51mm

For further information contact:

Securefast plc
 Unit 6 & 7
 The Cedars Business Centre
 Avon Road, Cannock
 Staffordshire
 WS11 1QJ



Call > +44 (0) 1704 502801

Email > sales@securefast.co.uk

Visit > www.securefast.co.uk