

Deedlock ANSI Mortice Electric Releases



The Deedlock ANSI Mortice Releases when used as an integral part of an electronic access control system, provides the physical means of securing the door.

ANSI mortice releases have an additional lip on the opening face which protects the recessed edge of the door frame. It provides a cleaner appearance and smoother operation.

Features & Benefits

- Suitable for low to medium traffic applications
- Fail locked and fail unlocked versions
- ANSI Mortice versions suitable for latches up to 15mm throw
- Jaw strengths up to 1000 lbs
- 12V DC or dual operation.
- The AST125-FLT and AST125-FUT are supplied with a short Aluminium faceplate for metal doors and a long stainless steel faceplate for timber doors .
- The AER125-SL is supplied with a stainless steel faceplate

Product Code	Max Latch Throw	Operating Voltage	Fail Locked / Unlocked	Additional info
AST125-FLT	15 mm	12V DC	Fail Locked	c/w Short & Long Faceplate
AST125-FUT	15 mm	12V DC	Fail Unlocked	c/w Short & Long Faceplate
AER125-SL	15 mm	12V DC	Fail Locked	Dual Monitored

For further information contact:

Securefast plc
 6, The Cedars Business Centre
 Avon Road, Cannock
 Staffordshire
 WS11 1QJ



Call > +44 (0) 1704 502 801

Email > sales@securefast.co.uk

Visit > www.securefast.co.uk