

### AKA-WCP3AG-SG IP67 Single Pole Break Glass Unit



**The waterproof range is IP67 sealed. The Intrinsically Safe WCP Call Point is intended for use in hazardous environments where protection against water ingress is also required. The Intrinsically Safe (IS) WCP3 has a single Normally Open / Normally Closed (NO/NC) contact for use with access control systems.**

The outdoor WCP is an IP67 sealed manual call point product. The enhanced environmental protection allows the unit to be installed in many external environments where water and dirt are likely to be present, making it a true waterproof and outdoor product.

#### Features & Benefits

- Sealed to IP67
- Unique 'Plug & Play' installation concept
- Total 'Flex-Ability' in the choice of operating element
- Anti-Tamper facility
- Enhanced aesthetics and compact design
- Fully approved to the latest standards
- CPD Approval
- Dimensions: 97.5 x 93 x 71mm
- Humidity: 0-93±3% non-condensing
- Operating Temperature: -250C to +700C
- Storage Temperature: -250C to +700C
- Approved to EN54-11 Standard

For further information contact:

**Securefast plc**  
6, The Cedars Business Centre  
Avon Road, Cannock  
Staffordshire  
WS11 1QJ



**Call** > +44 (0) 1704 502 801

**Email** > sales@securefast.co.uk

**Visit** > www.securefast.co.uk